Dual-Channel Thermocouple Thermometer

ZyTemp
A new way to measure temperature

TCTM01



- Dual Channel Thermocouple widely used to record and monitor temperature in industrial, freezer, engineering, lab, oven, HVAC, etc.
- Multi-functional: Max/ Min/ Average /Hold value and RH / DP / WB recording function and switchable between °C & °F.
- Mode selection (K/ T/ J/ E), 2 pieces AA Batteries powered with easy to replace.
- Specially designed "T1-T2" and Timer calculation function to facilitate users to easily find the difference between two samples.
- Large & Clear Backlit LCD Display for easily to check ambient data in time.
- Optional for Bluetooth, HAPPC, dry and wet bulb kit with more intuitive experience.

Note: The device is a temperature scanner, not a medical device.

T1/ T2 Slots	Diverse Measurement Modes
	 Max/Min/Average/Hold/RH/DP/WB/Timer Function

Measurement Range:	K-type -200°C to 1372°C (-328°F to 2502°F) T-type -250°C to 400°C (-418°F to 752°F) J-type -210°C to 1200°C (-346°F to 2192°F) E-type -150°C to 1000°C (-238°F to 1832°F)
Accuracy(Tamb=25°C):	above -100°C ±(0.05%+0.3°C)/-148 °F ±(0.05%+0.5°F) below -100°C ±(0.20%+0.3°C)/-148 °F ±(0.20%+0.5°F)
Operating Range:	-10~50°C (14~122°F)
Resolution:	0.1°C/0.1°F

Specifications are subject to change without notice


Factory


Industry


Laboratory


Food


HVAC



INNOVATION RADIANT
https://www.ZyTemp.com | https://www.ZyAura.com | https://www.Radiantek.com.tw
Add: 1F,No.3,Industrial E.9th Rd.,Science-Based Industrial Park, Hsin-Chu, Taiwan, 300 | Tel: +886(3)5644185 or 6111666 | Fax: +886(3)5644170

CE RoHS